

The bored tunnel will be two lanes in each direction with shoulders on each side.

All tunnels are not the same: SR 99 deep bored tunnel vs. the waterfront tunnel

WSDOT, King County and the City of Seattle plan to replace the central waterfront portion of the Alaskan Way Viaduct and Seawall with an approximately 2 mile-long deep bored tunnel beneath downtown, a new waterfront surface street, transit investments, and downtown and waterfront city street improvements.

While this bored tunnel and the cut-and-cover tunnel considered by Seattle voters in March 2007 are both tunnels, they are vastly different in their construction methods, length and degree of public disruption, and environmental effects.

Location and depth

The bored tunnel will be located several blocks inshore under First Avenue, bypassing the Battery Street Tunnel. The cut-and-cover tunnel would have roughly followed the path of the existing viaduct.


The bored tunnel will be at depths of 100-200 feet, while the cut-and-cover tunnel would have required excavation of 30-50 feet of soil.

Construction method and timeline

The bored tunnel will be drilled by a large tunnel boring machine, and most of the construction operations will occur from one location near the stadiums. The tunnel boring machine will be a new machine built specifically for this tunnel. Constructing the cut-and-cover tunnel would have meant digging up the entire street along Alaskan Way, temporarily rebuilding

Other central waterfront fact sheets include:

- Comparison of the Big Dig and the Alaskan Way Viaduct and Seawall Replacement Program
- Learning and listening: How the bored tunnel recommendation was developed
- Learning from local and international tunnel projects
- Public safety a top priority in bored tunnel



The bored tunnel will be located several blocks inshore under First Avenue.



For More Information:

Visit the Web site at:

www.alaskanwayviaduct.org

Call the hotline:

1-888-AWW-LINE

Send an e-mail to:

viaduct@wsdot.wa.gov

Send a letter to:

Alaskan Way Viaduct and Seawall
Replacement Program
c/o Washington State
Department of Transportation
999 Third Avenue, Suite 2424
Seattle, WA 98104

Printed 02/09

the street surface, then excavating beneath using conventional construction equipment. The time needed to excavate the deep bored tunnel will also be less than for the cut and cover tunnel.

Disruptions to the public

With cut-and-cover tunnel construction, we would have to demolish the viaduct first and reroute traffic to city streets for several years.

The public will experience much less disruption during bored tunnel construction, since the only openings to the surface will be at the ends of the tunnel. The bored tunnel concept will also allow traffic on the viaduct while the tunnel is being constructed.

In addition to the bored tunnel, restoration of the waterfront, including demolition of the viaduct, reconstruction of the seawall, required utility relocations, and construction of a new Alaskan Way and promenade, will be completed as separate projects.


Overall, the bored tunnel will result in substantially less traffic disruption both in length of time and intensity.

Environmental and archaeological impact

Because of its depth, the environmental and potential archaeological impact of a bored tunnel should be considerably less than that associated with a cut-and-cover tunnel.

Since cut-and-cover requires excavating the upper soils, we would have likely encountered difficult ground conditions along the tunnel's entire length. These conditions would have included very soft soils, miscellaneous man-made rubble, abundant old timbers, and a considerable volume of contaminated soil and groundwater.

The bored tunnel is expected to encounter uncontaminated dense natural glacial soils throughout most of its length. Construction activities will encounter challenging soil conditions primarily at its south entrance, which would have been true for the cut-and-cover tunnel as well.



Americans with Disabilities Act & Title VI information

Americans with Disabilities Act (ADA) Information: Materials can be provided in alternative formats: large print, Braille, cassette tape, or on computer disk for people with disabilities by contacting Heather Santic at 206-267-3789 / SanticH@wsdot.wa.gov. Persons who are deaf or hard of hearing may make a request for alternative formats through the Washington Relay Service at 7-1-1.

Title VI: WSDOT ensures full compliance with Title VI of the Civil Rights Act of 1964 by prohibiting discrimination against any person on the basis of race, color, national origin or sex in the provision of benefits and services resulting from its federally assisted programs and activities. For questions regarding WSDOT's Title VI Program, you may contact the Department's Title VI Coordinator at 360-705-7098.